


Rolamento de agulhas GBRI61816-U-IKO - GBRI61816-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbri61816-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)					
	With two seals	With one seal		d	D	C			
9.525 ($\frac{3}{8}$)	GBRI 61816 U		94.5	9.525 ($\frac{3}{8}$)	28.575 ($1\frac{1}{4}$)	25.400 (1)			
		Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring		
B	F _w	Min.	Max.	r _{as max} ⁽¹⁾	N	N			
25.650	15.875 ($\frac{5}{8}$)	14	14.5	24.5	0.6	23 500	28 500	5 000	LRBZ 61016

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952383286
Diâmetro interior	9.525 mm
Diâmetro exterior	28.575 mm
Espessura	25.4 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE