


## Rolamento de agulhas GBRI406028-UU-IKO - GBRI406028-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbri406028-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)					
	With two seals	With one seal		d	D	C			
63.500 (2 1/2)	GBRI 406028 UU		1 140	63.500 (2 1/2)	95.250 (3 7/8)	44.450 (1 3/4)			
B	F <sub>w</sub>	Standard mounting dimensions - mm			Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		d <sub>1</sub> Min.	d <sub>2</sub> Max.	D <sub>s</sub> Max.					r <sub>as max</sub> <sup>(1)</sup>
44.700	76.200 (3)	71	73	88	1.5	101 000	215 000	1 100	LRBZ 404828

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952383569
Diâmetro interior	63.5 mm
Diâmetro exterior	95.25 mm
Espessura	44.45 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE