


Rolamento de agulhas GBRI406028-U-IKO - GBRI406028-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbri406028-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)					
	With two seals	With one seal		d	D	C			
63.500 (2 1/2)	GBRI 406028 U		1 140	63.500 (2 1/2)	95.250 (3 7/8)	44.450 (1 3/4)			
		Standoff mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾	Assembled inner ring		
B	F _w	Min.	Max.	r _{as max} ⁽¹⁾	N	N	rpm		
44.700	76.200 (3)	71	73	88	1.5	101 000	215 000	1 100	LRBZ 404828

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952383576
Diâmetro interior	63.5 mm
Diâmetro exterior	95.25 mm
Espessura	44.45 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE