


## Rolamento de agulhas GBRI446828-U-IKO - GBRI446828-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbri446828-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)					
	With two seals	With one seal		d	D	C			
69.850 (2 3/4)	GBRI 446828 U		1 490	69.850 ± 0.010	107.950 ± 0.010	44.450 ± 0.010			
B	F <sub>w</sub>	Standard mounting dimensions mm			Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		Min.	Max.	D <sub>16</sub> Max.					r <sub>as max</sub> <sup>(1)</sup>
44.700	82.550 ± 0.010	77	79	99.9	1.5	127 000	231 000	950	LRBZ 446228

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952383583
Diâmetro interior	69.85 mm
Diâmetro interior	2 3/4" inch
Diâmetro exterior	107.95 mm
Diâmetro exterior	4 1/4" inch
Espessura	44.45 mm
Espessura	1 3/4" inch
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE