

## Rolamento de agulhas NAFW102220-IKO - NAW102220-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nafw102220-iko>

**IKO**  
**NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE**  
With Inner Ring



Shaft dia. mm	Identification number	Mess (Ref.) g	Boundary dimensions mm					Standard mounting dimensions mm				
			d	D	C	r <sub>s</sub> min <sup>(1)</sup>	F <sub>w</sub>	d <sub>b</sub> Max.	D <sub>s</sub> Min.	d <sub>s</sub> Max.	D <sub>b</sub>	
10	NAFW 102220	40	10	22	20	0.3	14	17.6	20	12	13	14.6
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>	Assembled roller ring									
N	N	rpm	LRT 101420									
10 800	14 200	35 000										

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952384382
Diâmetro interior	10 mm
Diâmetro exterior	22 mm
Espessura	20 mm
Embalagem	1
Padrão	Nenhuma norma

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE