

Rolamento de agulhas NAF152813-IKO - NAF152813-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/naf152813-iko>

IKO
NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE
With Inner Ring

| Shaft dia. mm | Identification number | Mess (Ref.) g | Boundary dimensions mm | | | | | Standard mounting dimensions mm | | | | |
|-----------------------------|---|---|------------------------|----|----|-----------------------------------|----------------|---------------------------------|---------------------|---------------------|----------------|------|
| | | | d | D | C | r _s min ⁽¹⁾ | F _w | d _b Max. | D _s Min. | d _a Max. | D _b | |
| 15 | NAF 152813 | 38.5 | 15 | 28 | 13 | 0.3 | 20 | 23.6 | 28 | 17 | 19 | 20.6 |
| Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ | Assembled outer ring | | | | | | | | | |
| N | N | rpm | LRT 152013 | | | | | | | | | |
| 9 590 | 13 500 | 25 000 | | | | | | | | | | |

Notes:
1) Minimum allowable value of chamfer dimension r.
2) Allowable rotational speed applies to grease lubrication.
Remark:
1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952384436 |
| Diâmetro interior | 15 mm |
| Diâmetro exterior | 28 mm |
| Espessura | 13 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE