


Rolamento de agulhas NAU4909-IKO - NAU4909-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nau4909-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings
Full Complement Roller Bearings



NAU49 TRU

| Shaft dia. mm | Identification number | | Mass (Ref.) g | Boundary dimensions mm | | | | | |
|-----------------------------|---|---|---------------|------------------------|----|----|--|----|----------------|
| | Full complement type | Caged type | | d | D | C | r ⁽¹⁾ r _{s min} | J | E _w |
| 45 | — | NAU 4909 | 260 | 45 | 68 | 22 | 0.6 | 51 | 61 |
| Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ | | | | | | | |
| N | N | rpm | | | | | | | |
| 24 800 | 32 800 | 8 000 | | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952385389 |
| Diâmetro interior | 45 mm |
| Diâmetro exterior | 68 mm |
| Espessura | 22 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE