


## Rolamento de agulhas TRU284530-IKO - TRU284530-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/tru284530-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings  
Full Complement Roller Bearings



| Shaft dia. mm                 | Identification number                     |   | Mass (Ref.) g | Boundary dimensions mm |    |    |                                     |      |                |
|-------------------------------|---|---|---------------|------------------------|----|----|-------------------------------------|------|----------------|
|                               | Full complement type                      | Caged type                                    |               | d                      | D  | C  | r <sup>(1)</sup> F <sub>s</sub> min | J    | E <sub>w</sub> |
| 28                            | ---                                       | TRU 284530                                    | 173           | 28                     | 45 | 30 | 0.3                                 | 31.5 | 39.5           |
| Basic dynamic load rating C N | Basic static load rating C <sub>0</sub> N | Allowable rotational speed <sup>(2)</sup> rpm |               |                        |    |    |                                     |      |                |
| 28 700                        | 43 800                                    | 12 000  |               |                        |    |    |                                     |      |                |

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DO PRODUTO

|                   |               |
|-------------------|---------------|
| Marca             | IKO           |
| Nº Ean13          | 3663952386058 |
| Diâmetro interior | 28 mm         |
| Diâmetro exterior | 45 mm         |
| Espessura         | 30 mm         |
| Embalagem         | 1             |

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE