


Rolamento de agulhas TRU426230-UU-IKO - TRU426230-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/tru426230-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings [With Seal]
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r ⁽¹⁾	J
42	—	TRU 426230UU	290	42	62	30	0.6	48
E_w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n ₂ r/min					
56.5	34 600	57 800	4 000					

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952386140
Diâmetro interior	42 mm
Diâmetro interior	1.654" inch
Diâmetro exterior	62 mm
Diâmetro exterior	2.441" inch
Espessura	30 mm
Espessura	1.181" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE