


## Rolamento de agulhas NAG4912-UU-IKO - NAG4912-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nag4912-uu-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings **[With Seal]**  
Full Complement Roller Bearings **[With Seal]**



NAG49-UU

Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r <sup>(1)</sup> min	J
60	NAG 4912UU	—	425	60	85	25	1	67
$E_w$	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed n <sub>g</sub> rpm					
77.5	50 300	84 300	2,000					

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
N° Ean13	3663952386256
Diâmetro interior	60 mm
Diâmetro exterior	85 mm
Espessura	25 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE