


Rolamento de agulhas NAU4926-UU-IKO - NAU4926-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nau4926-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings [With Seal]
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ min	J
130	—	NAU 4926UU	3 610	130	180	50	2	147
E _w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n ₂ rpm					
165.5	N	N	1,300					

Notes: (1) Minimum allowable value of chamfer dimension r.
(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
N° Ean13	3663952386690
Diâmetro interior	130 mm
Diâmetro exterior	180 mm
Espessura	50 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE