


## Rolamento de agulhas NAS5011-UU-NR-IKO - NAS5011-UU-NR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nas5011-uu-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
55	NAS 5011UU NR		1.15	55	90	94.8	46	45	34	5.5
<i>f</i>	<i>c</i>	<i>r</i> (1)	<i>J</i>	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed (2) rpm				
2.5	2	0.6	68	118 000	193 000	1 800				

Notes (1) Minimum allowable value of chamfer dimension *r*.  
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAS and NAU series with a bore diameter, *d*, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952386805
Diâmetro interior	55 mm
Diâmetro exterior	90 mm
Espessura	46 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE