


Rolamento de agulhas NAS5012-ZZ-NR-IKO - NAS5012-ZZ-NR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nas5012-zz-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
60		NAS 5012ZZNR	1.20	60	95	99.8	46	45	34	5.5
<i>f</i>	<i>c</i>	<i>r</i> mm	<i>J</i>	Basic dynamic load rating C N	Static load rating C ₀ N	Allowable rotational speed ^(*) rpm				
2.5	2	0.6	73	123 000	208 000	1 700				

Notes^(*) Minimum allowable value of chamfer dimension *r*
^(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAG and NAU series with a bore diameter, *d*, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952386829
Diâmetro interior	60 mm
Diâmetro interior	2.362" inch
Diâmetro exterior	95 mm
Diâmetro exterior	3.74" inch
Espessura	46 mm
Espessura	1.811" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE