


## Rolamento de agulhas NAS5014-ZZ-NR-IKO - NAS5014-ZZ-NR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nas5014-zz-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm							
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S	
70		NAS 5014ZZNR	1.90	70	110	114.5	54	53	42	5.5	
	f	c	r <sub>s</sub> mm <sup>(1)</sup>	J	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm				
	2.5	2	0.6	84	179 000	284 000	1 400				

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952386867
Diâmetro interior	70 mm
Diâmetro exterior	110 mm
Espessura	54 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE