


Rolamento de agulhas NAS5044-UU-NR-IKO - NAS5044-UU-NR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nas5044-uu-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
220	NAS 5044UU	NR	52.0	220	340	356	160	159	130	14.5
f	c	r _s mm ⁽¹⁾	J	Basic dynamic load rating C N	Static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm				
6	4	1.5	260	1 510 000	3 110 000	450				

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952387192
Diâmetro interior	220 mm
Diâmetro exterior	340 mm
Espessura	160 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE