

## Rolamento de agulhas NAX6040Z-IKO - NAX6040Z-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nax6040z-iko>

**IKO**

**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring  
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Shaft dia. mm	Identification number					
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g
60		NAX 6040Z	454	---	---	---
Boundary dimensions mm						
$F_w$	$D$	$D_1$	$D_2$	$L$	$H$	$r_{s \text{ min}}$
60	72	85	86.5	40	17	12
Basic load ratings						
Basic dynamic load rating $C$		Basic static load rating $C_0$		Allowable rotational speed <sup>(2)</sup>		
Radial		Axial		rpm		
47 500		41 400		4 000		

Notes:  
(1) Minimum allowable value of chamfer dimension  $r$   
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952390376
Diâmetro interior	60 mm
Diâmetro exterior	72 mm
Espessura	40 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE