

Rolamento de agulhas NBX6040Z-IKO - NBX6040Z-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nbx6040z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS
Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number													
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		Mass (Ref.) g		With dust cover	Mass (Ref.) g			
60	---		---		---		---		NBX 6040Z	538			
Boundary dimensions mm													
F_w	D	D_1	D_2	L	H	t_1	r_1 min.	d_f	Basic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽²⁾		
60	72	85	86.5	40	17	12	1	60	47 500	64 600	103 000	224 000	4 000

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952390529
Diâmetro interior	60 mm
Diâmetro exterior	72 mm
Espessura	40 mm
Embalagem	1
Padrão	Nenhuma norma

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE