

Rolamento de agulhas NAX7040Z-IKO - NAX7040Z-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nax7040z-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number														
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		Mass (Ref.) g		With dust cover					
	NAX 7040Z		606		—		—		—					
Boundary dimensions mm														
F_w	D	D_1	D_2	L	H	r_1 min.	d_f	Basic load rating C	Basic static load rating C_0					
70	85	95	96.5	40	18	11	1	70	85	55 500	43 100	120 000	101 000	3 500

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952390550
Diâmetro interior	70 mm
Diâmetro exterior	85 mm
Espessura	40 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE