

Rolamento de agulhas NAXI1425Z-IKO - NAXI1425Z-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/naxi1425z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number																
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		d	D	D _i					
	NAXI 1425Z	65.5	---	---	---	---										
14	NAXI 1425Z		65.5		---		---		14	26	30					
Boundary dimensions mm																
D ₂	L	B	H	I ₁	r ⁽¹⁾	r ⁽²⁾	d ₄	d ₅	Radial	axial	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽³⁾ rpm	Assembled inner ring LRT 141717		
31	25	17	9	8	0.3	0.3	17	25	16	12	900	10 800	16 300	14 500	8 500	LRT 141717

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952390734
Diâmetro interior	14 mm
Diâmetro exterior	26 mm
Espessura	31 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE