

Rolamento de agulhas NAXI1730-IKO - NAXI1730-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/naxi1730-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
17	NAXI 1730	99	—	—	—	—	17	30	35

Boundary dimensions mm				Bore chamfer mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring						
D ₂	L	B	H			Radial	Axial			Radial	Axial				
36	30	20.5	10	10.5	0.3	0.3	20	29	19	17 600	14 200	25 400	19 700	7 500	LRT 172020

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
 Remark 1: The outer ring has an oil groove and an oil hole.
 2: Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952390765
Diâmetro interior	17 mm
Diâmetro exterior	30 mm
Espessura	30 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE