

## Rolamento de agulhas NBXI2530-IKO - NBXI2530-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nbxi2530-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number								d	D	D <sub>i</sub>	
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g						
25	---	---	---	<b>NBXI 2530</b>	194	---	---	---	---	25	42	47

  

Boundary dimensions mm			Shoulder diameter mm	Shoulder radius mm	Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring									
D <sub>2</sub>	L	B			Radial	Axial	Radial	Axial											
48	30	20.5	11	9.5	0.6	0.3	30	45	25	100	27	400	40	100	81	000	8	000	LRT 253020

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952390864
Diâmetro interior	25 mm
Diâmetro exterior	42 mm
Espessura	30 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE