


Rolamento de agulhas NBXI3030Z-IKO - NBXI3030Z-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nbxi3030z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**



Shaft dia. mm	Identification number						d	D	D ₁	
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover				
30					NBXI 3030Z	232	30	47	52	
Boundary dimensions mm										
D ₂	L	B	H	I ₁	r	d ₄	d ₅	Radial	axial	Assembled inner ring
53	30	20	12	9	0.6	0.3	35	50	34	LRT 303520
Basic dynamic load rating C										
Basic static load rating C ₀										
Allowable rotational speed ⁽²⁾										

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: Z: The outer ring has an oil groove and an oil hole.
1: Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952390918
Diâmetro interior	30 mm
Diâmetro exterior	47 mm
Espessura	30 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE