

Rolamento de agulhas NAXI3532Z-IKO - NAXI3532Z-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/naxi3532z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
35		NAXI 3532Z	273	—	—	—	35	52	60

Boundary dimensions mm			r ⁽¹⁾ mm	r _{max} ⁽²⁾ mm	r _{min} ⁽²⁾ mm	d ₄ mm	d ₅ mm	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽³⁾ rpm	Assembled inner ring LRT 354020							
D ₂	L	B						Radial	Axial	Radial	Axial									
61	32	20	13	10	0.6	0.3	40	52	39	29	400	26	900	54	100	50	000	5	500	

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952390932
Diâmetro interior	35 mm
Diâmetro exterior	52 mm
Espessura	32 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE