

## Rolamento de agulhas NAXI4032-IKO - NAXI4032-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/naxi4032-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number								d	D	D <sub>i</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g			
40	<b>NAXI 4032</b>	315	—	—	—	—	—	—	40	58	65

  

Boundary dimensions mm				Bore chamfer mm	Bore chamfer mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring LRT 404520					
D <sub>2</sub>	L	B	H				Radial	Radial			Radial	Radial			
66.5	32	20	14	9	0.6	0.3	45	57	44	31 000	27 900	60 200	55 100	5 000	LRT 404520

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952390963
Diâmetro interior	40 mm
Diâmetro exterior	58 mm
Espessura	32 mm
Embalagem	-

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE