

## Rolamento de agulhas NBXI4032-IKO - NBXI4032-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nbxi4032-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**  
Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number															
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		Mass (Ref.) g	d	D	D <sub>i</sub>			
	NBXI 4032 344														
Boundary dimensions mm															
D <sub>2</sub>	L	B	H	I <sub>1</sub>	r <sup>(1)</sup>	r <sup>(2)</sup>	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	Radial	Axial	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(3)</sup>	Assembled inner ring
66.5	32	20	14	9	0.6	0.3	45	62	44	31 000	40 800	60 200	133 000	5 500	LRT 404520

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952390987
Diâmetro interior	40 mm
Diâmetro exterior	58 mm
Espessura	32 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE