

Rolamento de agulhas NBXI4535-IKO - NBXI4535-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/nbxi4535-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
45	---	---	NBXI 4535			366	45	62	70

Boundary dimensions mm				Bore chamfer mm	Bore chamfer mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRT 455025										
D ₂	L	B	H				Radial	Radial			Radial	Radial								
71.5	35	25	14	10	0.6	0.3	50	50	67	49	42	200	43	300	83	400	148	000	5	000

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remark 1: The outer ring has an oil groove and an oil hole.
Z: Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952391021
Diâmetro interior	45 mm
Diâmetro exterior	62 mm
Espessura	35 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE