

Rolamento de agulhas NAXI5040Z-IKO - NAXI5040Z-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/naxi5040z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number											
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		d	D	D _i
	NAXI 5040Z	619	—	—	—	—	—	—			
50	NAXI 5040Z		619		—		—		50	72	85

Boundary dimensions mm															
D ₂	L	B	H	I ₁	r ⁽¹⁾	r ⁽²⁾	d ₄	d ₅	C	C ₀					
Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽³⁾		Assembled inner ring									
Radial		Axial		Radial		Axial									
N		N		N		N									
86.5	40	25.5	17	12	1	1	60	75	59	47 500	41 400	103 000	89 700	4 000	LRT 506025

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remark 1: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952391052
Diâmetro interior	50 mm
Diâmetro exterior	72 mm
Espessura	40 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE