

Rótula GE SB9515082-IKO - SB9515082-IKO

<https://www.123rolamento.pt/rolamento-mancal/rotula/ge/sb9515082-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree		
			d	D	B	C	d_k ⁽¹⁾			
95	SB 9515082	6.05	95	150	82	70	140	0.6	5	
Mounting dimensions mm		Dynamic load capacity C_d N	Static load capacity C_s N							
d_s Min.	d_s Max. ⁽²⁾		D_s Min.							
99.5	113.5	145.5	130	961 000	5 770 000					

Notes ⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952391519
Diâmetro interior	95 mm
Diâmetro interior	3.74" inch
Diâmetro exterior	150 mm
Diâmetro exterior	5.906" inch
Espessura	82 mm
Espessura	3.228" inch
Tipo	GE
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE