

Rótula GE


GE80GS-2RS-IKO - GE80GS-2RS-IKO

<https://www.123rolamento.pt/rolamento-mancal/rotula/ge/ge80gs-2rs-iko>



SPHERICAL BUSHINGS

Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		A	D	B	C	d _s	r ₁ (1)	r ₂ (1)	α	α _l
80		GE 80GS-2RS	3.60	80	130	75	50	115	1	1	14	13
Mounting dimensions mm		Dynamic load capacity C _d		Static load capacity C _s								
d _s		D _s		N		N						
Min.	Max.(2)	Max.	Min.									
85.5	87	124.5	112	564 000		3 380 000						

Notes(1)

(2)

Remark(1)

Minimum allowable value of chamfer dimensions r₁ and r₂

When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.

The inner ring and the outer ring have an oil groove and two oil holes, respectively.

2.

Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
N° Ean13	3663952392455
Diâmetro interior	80 mm
Diâmetro exterior	130 mm
Espessura	75 mm
Tipo	GE
Peso	3500 g
Lubrificação	sem
Embalagem	1
Padrão	Nenhuma norma

contato@123rolamento.pt
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE