

Rótula GE GE80GS-IKO - GE80GS-IKO

<https://www.123rolamento.pt/rolamento-mancal/rotula/ge/ge80gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d _s	r ₁ ⁽¹⁾ mm	r ₂ ⁽¹⁾ mm	α	α ₁	
80	GE 80GS		3.60	80	130	75	50	115	1	1	14	13	
Mounting dimensions mm		Dynamic load capacity C _d		Static load capacity C _s									
d _s		D _s		N		N							
Min.	Max. ⁽²⁾	Max.	Min.										
85.5	87	124.5	112	564 000		3 380 000							

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
N° Ean13	3663952392462
Diâmetro interior	80 mm
Diâmetro exterior	130 mm
Espessura	75 mm
Tipo	GE
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE