


Rótula GE GE100GS-2RS-IKO - GE100GS-2RS-IKO

<https://www.123rolamento.pt/rolamento-mancal/rotula/ge/ge100gs-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
100		GE 100GS-2RS	6.15	100	160	85	55	140	1	1	14	12
Mounting dimensions mm		Dynamic load capacity C_d N	Static load capacity C_s N	d_s		D_s						
Min.	Max.(2)			Max.	Min.	Max.	Min.	Max.				
105.5	111	154.5	138	755 000	4 530 000							

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
N° Ean13	3663952392493
Diâmetro interior	100 mm
Diâmetro exterior	160 mm
Espessura	85 mm
Tipo	GE
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE