


Rótula GE GE140GS-2RS-IKO - GE140GS-2RS-IKO

<https://www.123rolamento.pt/rolamento-mancal/rotula/ge/ge140gs-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree				
	Without seals	With seals		d	D	B	C	d _s	r ₁ (1)	r ₂ (1)	α	α ₁		
140		GE 140GS-2RS	19.2	140	230	130	80	200	1	1	16	15		
Mounting dimensions mm		Dynamic load capacity C _d N	Static load capacity C _s N	d _s		D _s								
Min.	Max. (2)			Min.	Max.	Min.	Max.	Min.	Max.					
145.5	152	224.5	195	1 570 000										

Notes (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952392561
Diâmetro interior	140 mm
Diâmetro exterior	230 mm
Espessura	130 mm
Tipo	GE
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE