


Rótula GE GE160GS-IKO - GE160GS-IKO

<https://www.123rolamento.pt/rolamento-mancal/rotula/ge/ge160gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d_s	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
160	GE 160GS		25.4	160	260	135	80	225	1	1.1	16	14
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s								
d_s	D_s											
Min.	Max.(2)	Max.	Min.	N	N							
165.5	180	253	221	1 770 000	10 600 000							

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
N° Ean13	3663952392585
Diâmetro interior	160 mm
Diâmetro interior	6.299" inch
Diâmetro exterior	260 mm
Diâmetro exterior	10.236" inch
Espessura	135 mm
Espessura	5.315" inch
Tipo	GE
Lubrificação	sem
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE