


Rolo de leva CRY30-V-IKO - CRY30-V-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos-leva/cry30-v-iko>

IKO
ROLLER FOLLOWERS
Non-separable Roller Followers, Inch Series **Full Complement Type /With Inner Ring**



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions: mm(inch)			
	Shield type Cylindrical outer ring	Sealed type Cylindrical outer ring		d	D	B	C
12.700 (.50)	CRY 30 V		363	12.700 (f ₆)	47.625 (j ₆)	26.988 (1.0625)	25.400 (1)
		Shaft dia.			Basic dynamic load rating C		Basic static load rating C ₀
		Push fit		Drive fit		Press fit	
		Min.	Max.	Min.	Max.	Min.	Max.
		32.7(1.287)	1.588 (j ₅)	12.682	12.692	12.698	12.708
				12.708	12.708	12.718	35 300
						N	N
						35 300	55 600

Remarks: 1. The inner ring has an oil hole.
2. Provided with prepacked grease.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952398174
Diâmetro interior	12.7 mm
Diâmetro exterior	47.625 mm
Espessura	26.988 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE