


## Rolo de leva CRY26-VR-IKO - CRY26-VR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos-leva/cry26-vr-iko>

**IKO**  
**ROLLER FOLLOWERS**  
Non-separable Roller Followers, Inch Series **Full Complement Type /With Inner Ring**



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions: mm(inch)									
	Shield type Cylindrical outer ring	Sealed type Cylindrical outer ring		d	D	B	C						
11.112 ( $\frac{7}{16}$ )	<b>CRY 26 VR</b>		227	11.112 ( $\frac{7}{16}$ )	41.275 ( $1\frac{1}{2}$ )	23.813(0.9375)	22.225 ( $\frac{7}{8}$ )						
				Shaft dia.			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>					
				Push fit	Drive fit		Press fit	N	N				
				Min.	Max.	Min.	Max.	Min.	Max.				
				28.8(1.134)	500 (20)	11.095	11.105	11.110	11.120	11.115	11.125	28 200	40 100

Remarks: 1. The inner ring has an oil hole.  
2. Provided with prepacked grease.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952398853
Diâmetro interior	11.112 mm
Diâmetro exterior	41.275 mm
Espessura	23.813 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE