


Rolo de leva CRY36-VR-IKO - CRY36-VR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos-leva/cry36-vr-iko>

IKO
ROLLER FOLLOWERS
Non-separable Roller Followers, Inch Series **Full Complement Type /With Inner Ring**



Shaft dia. mm (inch)	Identification number		Mass (Ref.)	Boundary dimensions: mm(inch)			
	Shield type Cylindrical outer ring	Sealed type Cylindrical outer ring		<i>d</i>	<i>D</i>	<i>B</i>	<i>C</i>
15.875 ($\frac{5}{8}$)	CRY 36 VR		599	15.875 ($\frac{5}{8}$)	57.150 ($2\frac{1}{4}$)	33.338 (1.3125)	31.750 ($1\frac{1}{4}$)
		Shaft dia.			Basic dynamic load rating <i>C</i>		Basic static load rating <i>C₀</i>
<i>d</i>	<i>f</i>	Push fit		Drive fit		Press fit	
		Min.	Max.	Min.	Max.	Min.	Max.
38.0 (1.417)	600 ($\frac{24}{1}$)	15.857	15.867	15.873	15.883	15.883	15.893
						45 700	80 600

Remarks: 1. The inner ring has an oil hole.
2. Provided with prepacked grease.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952398938
Diâmetro interior	15.875 mm
Diâmetro exterior	57.15 mm
Espessura	33.338 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE