

## Rolamento cónico 33124-JR-JTEKT - 33124-JR-KOYO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/33124-jr-koyo>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |                      | Bearing No. <sup>1)</sup> |                    |                |                      |      |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|----------------------|------|
| d                                      | D                  | T                        | B                    | C                       | C <sub>r</sub>       | C <sub>0r</sub>      | Grease lub.          | Oil lub.                             |                      |                           |                    |                |                      |      |
| 120                                    | 200                | 62                       | 62                   | 48                      | 482                  | 785                  | 1 800                | 2 400                                | 33124JR              |                           |                    |                |                      |      |
| Dimension series to ISO 955 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                         |                      |                      |                      |                                      |                      | Constant e                | Axial load factors |                | (Refer. 1) Mass (kg) |      |
|  |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | D <sub>1a</sub> min.    | D <sub>1a</sub> max. | S <sub>1a</sub> min. | S <sub>1a</sub> max. | r <sub>3a</sub> min.                 | r <sub>3a</sub> max. |                           | Y <sub>1</sub>     | Y <sub>0</sub> |                      |      |
| 3FE                                    | 47.8               | 132                      | 133                  | 190                     | 172                  | 192                  | 9                    | 14                                   | 2                    | 2                         | 0.40               | 1.51           | 0.83                 | 7.73 |

### CARACTERÍSTICAS DO PRODUTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| Nº Ean13          | 3663952411385 |
| Diâmetro interior | 120 mm        |
| Diâmetro exterior | 200 mm        |
| Espessura         | 62 mm         |
| Embalagem         | 1             |

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE