

Rolo de leva com eixo

CF8-VUUM-IKO - CF8-VUUM-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cf8-vuum-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



| Stud dia.<br>mm | Identification number   |  |                             |  |                         |  |                             |  | Mass (Ref.) |    |    |                |
|-----------------|-------------------------|--|-----------------------------|--|-------------------------|--|-----------------------------|--|-------------|----|----|----------------|
|                 | Shield type             |  |                             |  | Sealed type             |  |                             |  | g           | D  | C  | d <sub>1</sub> |
|                 | With crowned outer ring |  | With cylindrical outer ring |  | With crowned outer ring |  | With cylindrical outer ring |  |             |    |    |                |
| 8               |                         |  |                             |  | CF 8 VUUM               |  |                             |  | 29          | 19 | 11 | 8              |

  

| Boundary dimensions mm |                |                  |                   |                |                |                |                |                |                  |    | Working dimension<br>f <sub>min</sub><br>mm | Maximum<br>tightening<br>torque<br>N·m | Basic dynamic<br>load rating<br>C<br>N | Basic static<br>load rating<br>C <sub>0</sub><br>N | Maximum<br>allowable<br>static load<br>N |
|------------------------|----------------|------------------|-------------------|----------------|----------------|----------------|----------------|----------------|------------------|----|---------------------------------------------|----------------------------------------|----------------------------------------|----------------------------------------------------|------------------------------------------|
| G                      | G <sub>1</sub> | B <sub>max</sub> | B <sub>1max</sub> | B <sub>2</sub> | B <sub>3</sub> | C <sub>1</sub> | g <sub>1</sub> | g <sub>2</sub> | r <sub>max</sub> |    |                                             |                                        |                                        |                                                    |                                          |
| M 8×1                  | 10             | 12.2             | 32.2              | 20             | —              | 0.6            | *4             | —              | 0.3              | 13 | 7.1                                         | 8 170                                  | 11 200                                 | 4 620                                              |                                          |

CARACTERÍSTICAS DO PRODUTO

|                   |               |
|-------------------|---------------|
| Marca             | IKO           |
| Nº Ean13          | 3663952440224 |
| Diâmetro interior | 8 mm          |
| Diâmetro exterior | 19 mm         |
| Espessura         | 11 mm         |
| Embalagem         | 1             |

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)  
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE