


Rolo de leva com eixo CF16-VUUR-IKO - CF16-VUUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cf16-vuur-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



CF-VUUR

Stud dia. mm	Identification number								Mass (Ref.)				
	Shield type				Sealed type				g	D	C	d ₁	
	With crowned outer ring		With cylindrical outer ring		With crowned outer ring		With cylindrical outer ring						
16			CF 16		VUUR				173	35	18	16	
Boundary dimensions mm													
G	G ₁	B _{max}	B _{1max}	B ₂	B ₃	C ₁	g ₁	g ₂	f ⁽¹⁾ Min. mm	Mounting torque C N·m	Basic dynamic load rating C ₀ N	Basic static load rating C ₀ N	
M16×1.5	17	19.6	52.1	32.5	8	0.8	6	3	0.6	26	58.5	20 700	37 600
Maximum allowable static load													
										23 200			

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060458568
Diâmetro interior	16 mm
Diâmetro exterior	35 mm
Espessura	18 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE