


Rolo de leva com eixo CF24-V-IKO - CF24-V-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cf24-v-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d ₁
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
24	CF24 V				820	62	29	24

Boundary dimensions mm								Mounting diameter f mm	Maximum tightening torque C N·m	Basic static load rating C ₀ N	Basic dynamic load rating C N	
G	G ₁	B max	B ₁ max	B ₂	B ₃	C ₁	g ₁ g ₂					
M24×1.5	25	30.6	80.1	49.5	11	0.8	8 4 1	40	215	48 600	92 000	52 000

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952440644
Diâmetro interior	24 mm
Diâmetro exterior	62 mm
Espessura	29 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE