

Rolo de leva com eixo CF5-R-IKO - CF5-R-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cf5-r-iko>

IKO
CAM FOLLOWERS
Standard Type Cam Followers With Cage/With Screwdriver Slot

| Stud dia. mm | Identification number | | | | Mass (Ref.) | | | | |
|-----------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|----|---|----------------|---------|
| | Shield type | | Sealed type | | g | D | C | d ₁ | G |
| | With crowned outer ring | With cylindrical outer ring | With tapered outer ring | With cylindrical outer ring | | | | | |
| 5 | CF | 5 | R | | 10.3 | 13 | 9 | 5 | M 5×0.8 |

| Boundary dimensions mm | | | | | | | | | | | | | |
|------------------------|----|----------------|----------------|----------------|----------------|----------------|----------------|---------------------------|-----------------|--------------------------------------|---------------------------------------|---|--|
| G ₁ | B | B ₁ | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | r _s max (°) | f Min. mm | Maximum ignoring stress N·m | Ball dynamic load rating C N | Ball static load rating C ₀ N | Maximum allowable static load N |
| 7.5 | 10 | 23 | 13 | — | 0.5 | *3.1 | — | 0.3 | 9.3 | 1.6 | 2 520 | 2 140 | 1 260 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952440910 |
| Diâmetro interior | 5 mm |
| Diâmetro exterior | 13 mm |
| Espessura | 9 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE