


## Rolo de leva com eixo CF8-M-IKO - CF8-M-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cf8-m-iko>



### CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF

Stud dia. mm	Identification number				Mass (Ref.)				
	Shield type		Sealed type		g	D	C	d <sub>1</sub>	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
<b>8</b>	<b>CF 8 M</b>				28.5	19	11	8	M 8×1

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum ignoring torque N·m	Ball dynamic load rating C N	Ball static load rating C <sub>0</sub> N	Maximum allowable static load N
G <sub>1</sub>	B	B <sub>1</sub>	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>	r <sub>s</sub> max	(°)					
10	12.2max	32.2max	20	—	0.6	*4	—	0.3	13	7.1	4 250	4 740	4 620	

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952441047
Diâmetro interior	8 mm
Diâmetro exterior	19 mm
Espessura	11 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE