


Rolo de leva com eixo CF18-UU-IKO - CF18-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cf18-uu-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UU

Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d ₁	G
	Shield type		Sealed type						
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
18				CF 18 UU	250	40	20	18	M18×1.5

Boundary dimensions mm										Mounting torque N·m	Ball dynamic load rating C	Ball static load rating C ₀	Maximum allowable static load N
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max	(*) f Min. mm				
19	21.6max	58.1max	36.5	8	0.8	6	3	1	29	86.2	14 800	25 200	25 200

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952441399
Diâmetro interior	18 mm
Diâmetro exterior	40 mm
Espessura	20 mm
Embalagem	-

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE