


Rolo de leva com eixo CF30-IKO - CF30-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cf30-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF

Stud dia. mm	Identification number				Mass (Ref.)		D	C	d ₁	G
	Shield type		Sealed type		g	N				
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
30	CF 30				1 870	80	35	30	M30×1.5	

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum ignoring stress N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N	
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _{max}	(°)						
32	37	max	100	max	63	15	1	8	4	1	49	438	45 400	85 100	85 100

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952441573
Diâmetro interior	30 mm
Diâmetro exterior	80 mm
Espessura	35 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE