


Rolo de leva com eixo CF30-UUR-IKO - CF30-UUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cf30-uur-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UUR

Stud dia. mm	Identification number				Mass (Ref.)										
	Shield type		Sealed type		g	D	C	d ₁	G						
30	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	1 870	80	35	30	M30×1.5						
CF 30 UUR															
Boundary dimensions mm															
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max	(°)	f _{min} mm	Maximum ignoring stress N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N	
32	37	max	100	max	63	15	1	8	4	1	49	438	45 400	85 100	85 100

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952441580
Diâmetro interior	30 mm
Diâmetro exterior	80 mm
Espessura	35 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE