


Rolo de leva com eixo CF30-1-UUR-IKO - CF30-1-UUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cf30-1-uur-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UUR

Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d ₁	G
	Shield type		Sealed type						
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
30				CF 30-1 UUR	2 030	85	35	30	M30×1.5

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum tightening torque N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N	
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max	(°)						
32	37	max	100	max	63	15	1	8	4	1	49	438	45 400	85 100	85 100

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952441627
Diâmetro interior	30 mm
Diâmetro interior	1.181" inch
Diâmetro exterior	85 mm
Diâmetro exterior	3.346" inch
Espessura	35 mm
Espessura	1.378" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE