


## Rolo de leva com eixo CF8-VBM-IKO - CF8-VBM-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cf8-vbm-iko>



### CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Hexagon Hole



Stud dia. mm	Identification number								Mass (Ref.)			
	Shield type				Sealed type				g	D	C	d <sub>1</sub>
	With crowned outer ring		With cylindrical outer ring		With crowned outer ring		With cylindrical outer ring					
8	CF 8		VBM						29	19	11	8

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N	
G	G <sub>1</sub>	B max	B <sub>1</sub> max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	B <sub>2</sub>	H <sup>(*)</sup> mm						
M 8×1	10	12.2	32.2	20	—	0.6	—	—	4	0.3	13	7.1	8 170	11 200	4 620

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952441795
Diâmetro interior	8 mm
Diâmetro exterior	19 mm
Espessura	11 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE