


Rolo de leva com eixo CF8-BM-IKO - CF8-BM-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cf8-bm-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Hexagon Hole



CF-B

Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d ₁	G
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With groove outer ring	Sealed type With cylindrical outer ring					
8		CF 8 BM			28.5	19	11	8	M 8×1

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum spinning torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	H	r _s μm					
10	12.2max	32.2max	20	—	0.6	—	—	4	0.3	13	7.1	4 250	4 740	4 620

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952442631
Diâmetro interior	8 mm
Diâmetro exterior	19 mm
Espessura	11 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE