

Rolo de leva com eixo CFES8-UUR-IKO - CFES8-UUR-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfes8-uur-iko>

IKO
CAM FOLLOWERS
Solid Eccentric Stud Type Cam Followers With Cage/With Screwdriver Slot

Stud dia. mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d ₁
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
8			CFES 8	UUR	28.5	19	11	8

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
G	G ₁	B _{max}	B ₁	B ₂	B ₃	C ₁	B ₁	B ₂	α _{max} (°)						
M 8×1.25	10	12.2	32.2	20	—	0.6	*4	—	0.3	0.25	13	6.5	4 250	4 740	4 670

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060459107
Diâmetro interior	8 mm
Diâmetro exterior	19 mm
Espessura	11 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE