

Rolo de leva com eixo CFES12-IKO - CFES12-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/rolo-leva-eixo/cfes12-iko>

IKO
CAM FOLLOWERS
Solid Eccentric Stud Type Cam Followers With Cage/With Screwdriver Slot

Stud dia. mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d ₁
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
12	CFES 12				95	30	14	12

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum tightening torque N·m	Back dynamic load rating C N	Back static load rating C ₀ N	Maximum allowable static load N	
G	G ₁	B max	B ₁ max	B ₂	B ₃	C ₁	B ₁	B ₂	α ₂						
M12×1.5	13	15.2	40.2	25	6	0.6	6	3	0.6	0.4	21	21.9	7 910	9 790	9 790

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060459213
Diâmetro interior	12 mm
Diâmetro exterior	30 mm
Espessura	14 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE